

# National Auto Fleet Group

A Division of Chevrolet of Watsonville

490 Auto Center Drive, Watsonville, CA 95076

(855) 289-8572 • (831) 480-8497 Fax Fleet@NationalAutoFleetGroup.com

10/29/2024

Quote ID#3075HD

Town of Munster 508 Fisher Street Munster, IN 46321

Dear Town of Munster,

National Auto Fleet Group is pleased to quote the following sourced item(s) for your consideration. One (1) New/Unused (2026 Western Star 47X, Cummins L9 370HP Engine, Allison 3000 RDS Transmission Galion Patriot 14' Hardox Dump Body) and provided by Mr. Denny McIntyre with WA Jones, each for:

Contract Price

Chassis and Option W.A. Jones Quote Tax (0.00%)

\$ 140,776 \$ 127,464 0.00

Total

\$ 268,240.00

This sourced item(s) is available under the Sourcewell (Formerly Known as NJPA) Contract 032824-NAF. Please reference this Bid Number on all Purchase Orders.

Note price includes Trade in of existing town's truck.

Thank you in advance for your consideration. Should you have any questions, please do not hesitate to call. Sincerely,

Ben Rodriguez
Contract Manager
BEN@NationalAutoFleetGroup.com

Office (855) 289-6572 Fax (831) 480-8497









DODGE

# W.A. Jones

TRUCK BODIES & EQUIPMENT

Columbia City, IN Indianapolis, IN New Haven, IN

www.wajonestruckequipment.com

## **QUOTATION FOR**

Munster Street Department Russ Kozyra 508 Fisher Street Munster, IN 46321

E-Mail:

rkozyra@munster.org

Phone:

(219) 836-6976

Quote #

MACQ5612

Fax:

Delivery:

(219) 836-8350

Date:

10/24/2024

Salesman:

Denny McIntyre

#### Description

Provide And Install Following Galion Patriot 14' Stainless Body Floor 1/4" Ar 450 Hardox Sides 7 Gauge Stainless Steel Lined With 1/8" Hardox Liner Front Telescopic Liner With Double Acting Hoist Air Tailgate 6 Panel Sloped Tailgate Inside Step With Outside Steps And Grab Handles 2 Body Props 1/2 Cab Protector Shovel Holders Mud Flaps Per Specifications

Towing Operation To Have 3/4" Welded Plate Between Frame Rails And 25 Ton Pintle Hitch With Trailer Wiring Plug And Electric Brake Controller:

Central Hydraulic System To Be Certified Power Two Joystick Arm Rest / Valve Functions To Operate Plow Up, Down, Right, Left And Dump Body Up & Down: Pto Off The Chassis Transmission

Emergency Light System To Operate Thru Power Distribution Box/ 6 Amber /clear Led Lights In Cab Shield Facing Forward / 6 Led Amber Clear Facing Rear Ward In The Cab Shield / One Led Amber Clear In Body Rail Mid Point Each Side / Rear Post To Be Top Amber Clear Strobe 2nd From Top To Be Stop Tail Brake / 3rd From Top To Be Stop Tail Brake Reverse Combination/ One Rear Work Light Mounted On The Rear/ Plow Lights To Be Off The Chassis Hood And Will Be Heated Led:

Plow And Front Hitch Monroe Mte 10' Trip Reversible 41" Tall Mailbox Cut Out Right Side Hitch Mteq Rubber Snow Deflector Curb Guard Kit Markers 4x 10 Double Acting Cylinder

**Qty Unit Price** 

Ext. Price

\$127,464.00

\$127,464.00

SubTotal \$127,464.00 Sales Tax \$0.00 Total \$127,464.00

We appreciate the opportunity to submit this quoation. Please review it carefully. If there are any errors or changes please advise us. This quote shall be valid for a period not to exceed 30 days. THANK YOU. W. A. JONES TRUCK BODIES & EQUIPMENT

Columbia City Office 1171 S Williams Street Columbia City, IN 46725 Phone. 888-660-7661 Fax: 260-244-7662

Indianapolis Office 2102 Clay Street Indianapolis, IN 46205 Phone: 317-377-0407 Fax 317-377-0427

**New Haven Office** P O Box 558 New Haven, IN 46774 Phone: 260-748-4100 Fax: 250-748-4121

Page 1

A proposal for WA Jones

Prepared by **Truck Centers, Inc.**Dustin Waters

Oct 29, 2024

### Western Star 47X



Components shown may not reflect all spec'd options and are not to scale

# SPECIFICATION PROPOSAL

	Description	Weight Front	Weight Rear	
Price Level		THE REPORT OF		
	WST 47X/49X PRL-29X (EFF:MY26 ORDERS)	1041		
Data Version				SIN SI
	SPECPRO21 DATA RELEASE VER 014			
Vehicle Configura	tion			ALTERNATION OF
	WESTERN STAR 47X	9,050	6,525	
	2026 MODEL YEAR SPECIFIED	.,	5,020	
	SET BACK AXLE - TRUCK			
	TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560	10	10	
	LH PRIMARY STEERING LOCATION			
General Service	THE PROPERTY OF THE PARTY OF TH	-	100 St. St. 100 C	S CHICAGO
	TOLION TO A U. C.D. CONTROL OF THE C			

TRUCK/TRAILER CONFIGURATION

DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)

**EPA EMISSIONS CERTIFICATION FOR** REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR)

UTILITY/REPAIR/MAINTENANCE SERVICE

**GOVERNMENT BUSINESS SEGMENT** 

DIRT/SAND/ROCK COMMODITY

TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS

**MAXIMUM 8% EXPECTED GRADE** 

SMOOTH CONCRETE OR ASPHALT PAVEMENT -MOST SEVERE IN-TRANSIT (BETWEEN SITES)

ROAD SURFACE

WESTERN STAR VOCATIONAL WARRANTY EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs

EXPECTED REAR DRIVE AXLE(S) LOAD:

40000.0 lbs

	Description	Weight Front	Weight Rear	
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 58000.0 lbs			
	EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs			
Truck Service				E DELL'
	FRONT PLOW/END DUMP BODY			
	VIKING-CIVES MIDWEST			
Tractor Service				Sec. Sec.
	FLATBED TRAILER			7341
	SINGLE (1) TRAILER			
Engine	DESCRIPTION OF THE PARTY.			K. Samu
	CUM L9 370 HP @ 2100 RPM; 2100 GOV RPM, 1250 LB-FT @ 1200 RPM	-850	-70	
<b>Electronic Paramete</b>	rs Carlotte Carlotte			1180-1843
	70 MDH BOAD SEECD LIMIT		THE RESERVE OF	

70 MPH ROAD SPEED LIMIT

CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT

SHEED FIMIL

PTO MODE ENGINE RPM LIMIT - 1800 RPM PTO RPM WITH CRUISE SET SWITCH - 1100

RPM

PTO RPM WITH CRUISE RESUME SWITCH - 800

**RPM** 

PTO GOVERNOR RAMP RATE - 100 RPM PER

**SECOND** 

ONE REMOTE PTO SPEED

PTO SPEED 1 SETTING - 1100 RPM

AUTOMATIC OIL LIFE MONITOR WITH ALERT AT

5% OF INTERVAL REMAINING

PTO MINIMUM RPM - 700

PTO 1, NO SWITCH, TEM SUPPLIED REQUEST AND INTERLOCK, WITH PTO CONNECTIONS, NO

**INTERLOCKS** 

ENGINE MOUNT PTO, TEM SUPPLIED REQUEST

#### **Engine Equipment**

EPA 2010/GHG 2024 CONFIGURATION

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED HIGH CAPACITY AIR CLEANER, PASSIVE PRECLEANER, WITH INSIDE/OUTSIDE

AIR AND SNOW DOOR

10

Description	Weight Front	Weight Rear
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	-10	
(3) DTNA GENUINE, HIGH TEMP AGM STARTING AND CYCLING, MIN 2775CCA, 570RC, THREADED STUD BATTERIES		
PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE OF CAB		
BATTERY BOX MOUNTED UNDER PASSENGER SEAT		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
PLASTIC BATTERY BOX COVER		
NON-ESSENTIAL POSITIVE LOAD DISCONNECT, IN CAB CONTROL SWITCH MOUNTED OUTBOARD OF DRIVER SEAT	2	
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH		
11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
8 GALLON DIESEL EXHAUST FLUID TANK		
POLISHED ALUMINUM DIAMOND PLATE WST DIESEL EXHAUST FLUID TANK COVER		
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD		

	Description	Weight Front	Weight Rear	
	AIR POWERED ON/OFF ENGINE FAN CLUTCH			
	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED			
	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR AND 12 VOLT PREHEATER	10		
	CUMMINS SPIN ON FUEL FILTER			
	FULL FLOW OIL FILTER			
	1400 SQUARE INCH VOCATIONAL RADIATOR WITH PROTECTION PACKAGE	20		
	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			
	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
	STANDARD CHARGE AIR COOLER PLUMBING			
	RADIATOR DRAIN VALVE			
	LOWER RADIATOR GUARD			
	NO REPTO, EXTENDED FLYWHEEL HOUSING, CUML9 REQUIRED FOR PACKAGING			
	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4		
	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
	ELECTRIC GRID AIR INTAKE WARMER			
	DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	<b>-4</b> 5		
Transmission	THE RESERVE AND THE PARTY OF TH			
	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	-230	-130	
Transmission Equ	lineart Control of the Control of th			

#### **Transmission Equipment**

ALLISON VOCATIONAL PACKAGE 223 -AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV

ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

Description		Weight Front	Weight Rear
PRIMARY SHIFT SCHEDU DTNA AND ALLISON, THIS AND VOCATIONAL USAGI	DEFINED BY ENGINE		real
SECONDARY SHIFT SCHE RECOMMENDED BY DTN/ DEFINED BY ENGINE AND	AND ALLISON, THIS		
PRIMARY SHIFT SPEED R DTNA AND ALLISON, THIS AND VOCATIONAL USAGE	DEFINED BY ENGINE		
SECONDARY SHIFT SPEE DTNA AND ALLISON, THIS AND VOCATIONAL USAGE	DEFINED BY ENGINE		
FUEL SENSE 2.0 PLUS - D PERFORMANCE, NEUTRA	YNACTIVE: L AT STOP: ACTIVE		
QUICKFIT BODY LIGHTING CAB, WITH BLUNTCUTS	CONNECTOR UNDER		
ELECTRONIC TRANSMISS CUSTOMER INTERFACE C	ONNECTOR		
CUSTOMER INSTALLED C PTO	HELSEA 280 SERIES		
PTO MOUNTING, LH SIDE TRANSMISSION ALLISON	OF MAIN		
MAGNETIC PLUGS, ENGIN TRANSMISSION DRAIN, AX DRAIN	E DRAIN, (LE(S) FILL AND		
HEAVY DUTY ELECTRONIC SHIFT CONTROL, COLUMN	CTRANSMISSION MOUNTED		
WATER TO OIL TRANSMIS	SION COOLER		
TRANSMISSION OIL CHECI ELECTRONIC OIL LEVEL C	K AND FILL WITH HECK		
SYNTHETIC TRANSMISSIO COMPLIANT)	N FLUID (TES-295		
Front Axle and Equipment			PLANT STORY
DETROIT DA-F-18.0-5 18,00 DROP SINGLE FRONT AXLI	0# FL1 71.0 KPI/3.74	90	
CONMET PRESET PLUS PR HUBS	EMIUM IRON FRONT	20	
MERITOR 16,5X6 Q+ CAST : BRAKES, DOUBLE ANCHOF SHOES	SPIDER CAM FRONT C, FABRICATED	10	
NON-ASBESTOS FRONT BE	AKE LINING		
CONMET CAST IRON FRON	T BRAKE DRUMS		
FRONT BRAKE DUST SHIEL	DS	5	
FRONT OIL SEALS			

	Description	Weight Front	Weight Rear
	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
	HALDEX AUTOMATIC FRONT SLACK ADJUSTERS		
	DUAL POWER STEERING GEARS, BENDIX 16- 20K	80	
	4 QUART POWER STEERING RESERVOIR	5	
	OIL/AIR POWER STEERING COOLER	5	
	CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE		
Front Suspension			
	20,000# TAPERLEAF FRONT SUSPENSION	145	
	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION	.,.	
	FRONT SHOCK ABSORBERS		
Rear Axle and Equip	pment	2000	
	MERITOR RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE WITH PUMP		500
	CONMET PRESET PLUS PREMIUM ALUMINUM REAR HUBS		
	5.63 REAR AXLE RATIO		
	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
	MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-60	-60
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		30
	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD- REAR AND REAR-REAR AXLE VALVE		
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH		
	INDICATOR LIGHT AND BUZZER FOR EACH DIFFERENTIAL LOCKOUT SWITCH		
	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
	NON-ASBESTOS REAR BRAKE LINING		
	ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY		
	CONMET CAST IRON REAR BRAKE DRUMS		

7	Description	Weight Front	Weight Rear
	REAR BRAKE DUST SHIELDS		10
	REAR OIL SEALS		
	BENDIX EVERSURE LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		
	HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
EQUIPMENT OF THE PARTY.	STANDARD REAR AXLE BREATHER(S)		
Rear Suspension			
	HENDRICKSON HAULMAAX EX 46,000# REAR SUSPENSION		115
	10.8 INCH NOMINAL RIDE HEIGHT (490MM GLOBAL REFERENCE HEIGHT)		
	54 INCH AXLE SPACING		
	HENDRICKSON HN, HAULMAAX AND ULTIMAAX SERIES STEEL BEAMS WITH BAR PIN		
	STANDARD DUTY FORE/AFT AND HEAVY DUTY TRANSVERSE CONTROL RODS		
	DOUBLE REBOUND STRAP - INBOARD AND OUTBOARD		13
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)		
Pusher / Tag Equips	ment		
	NO PUSHER/TAG BRAKE DUST SHIELDS		
Brake System	NAME OF THE PARTY		
	WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH		
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
	WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE		
	WABCO OIL COALESCING FILTER FOR AIR DRYER		
	AIR DRYER MOUNTED UNDER HOOD		
	STEEL AIR BRAKE RESERVOIRS		
	PULL CABLES ON ALL AIR RESERVOIR(S)		
<b>Trailer Connections</b>			No. of the Party o
	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND DUST COVERS		

Application Version 11.9.905 Data Version PRL-29X.014 Town of Munster

10/29/2024 9:03 AM

	Description	Weight Front	Weight Rear	
	(1) QUICKFIT PROGRAMMABLE SOLENOID W/STATE RETENTION PLUMBED TO BACK OF CAB			
	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			
	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME			
	NO TRAILER ELECTRICAL CABLE	-10		
Wheelbase & Frame				To Take
	4725MM (186 INCH) WHEELBASE			426
	13.0MM X 87.0MM X 311.0MM STEEL FRAME (0.51X3.43X12.24 INCH) 120 KSI	120	410	
	1900MM (75 INCH) REAR FRAME OVERHANG			
	FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-50	160	
	24 INCH INTEGRAL FRONT FRAME EXTENSION	120		
	CALC'D BACK OF CAB TO REAR SUSP C/L (CA):	,		
	CALC'D FRAME LENGTH - OVERALL: 329.76 in			
	FRAME HEIGHT TOP FRONT UNLADEN: 46.5 in			
	FRAME HEIGHT TOP FRONT LADEN: 42.68 in			
	FRAME HEIGHT TOP REAR UNLADEN: 44.65 in			
	FRAME HEIGHT TOP REAR LADEN: 42.36 in			
	SQUARE END OF FRAME			
	STANDARD WEIGHT ENGINE CROSSMEMBER			
	STANDARD CAST ALUMINUM CROSSMEMBER BACK OF TRANSMISSION	-15		
	STANDARD CAST ALUMINUM MIDSHIP			
	HEAVY DUTY REAR CROSSMEMBER		70	
	STANDARD SUSPENSION CROSSMEMBER		20	
	CAST ALUMINUM REAR SUSPENSION CROSSMEMBER			
Chassis Equipment				ALC: NO.
	POLISHED ALUMINUM DIAMOND PLATE WST EQUIPMENT COVERS			
	CLEAR FRAME SPACE REQUESTED			
	PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL BUMPER	40		
	FRONT TOW HOOKS - FRONT FRAME EXTENSION MOUNTED			

	Description	Weight Front	Weight Rear
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
	CLASS 10.9 THREADED METRIC FASTENERS		
	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE		
	UPFIT ROUTING AND CLIPPING BRACKET, LH, BOC TO SUSPENSION, UPPER & LOWER SUPPORTS		
	UPFIT ROUTING AND CLIPPING BRACKET, RH, BOC TO SUSPENSION, UPPER & LOWER SUPPORTS		
Fuel Tanks			
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH	10	V
	25 INCH DIAMETER FUEL TANK(S)		
	POLISHING OF FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS		
	FUEL TANK(S) FORWARD		
	POLISHED STEP FINISH		
	CHROME FUEL TANK CAP(S)		
	EQUIFLO INBOARD FUEL SYSTEM		
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires			Carrier Co.
	CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY RADIAL FRONT TIRES	100	Service of the servic
	CONTINENTAL INTELLIGENT HDC3 11R22.5 16 PLY RADIAL REAR TIRES		192
Wheels			ALC: NO THE RESERVE
	ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS	66	TO SERVICE OF SERVICE
	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2- HAND HD STEEL DISC REAR WHEELS		104
	FRONT WHEEL MOUNTING NUTS		
	REAR WHEEL MOUNTING NUTS		
	NYLON WHEEL GUARDS BETWEEN REAR DUAL WHEELS ONLY		
Cab Exterior			
	111.6 INCH BBC CONVENTIONAL ALUMINUM CAB		
	STAINLESS STEEL CAB ACCENT MOLDING		
	FRONT FENDERS		

Description	Weight Front	Weight Rear	
BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	10		
SAFETY YELLOW INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANLDES			
BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS			
X-SERIES STEEL REINFORCED ALUMINUM CAB			
X-SERIES VOCATIONAL HOOD			
HOOD OPENING ASSIST WITH LOCKING STRUT			
WESTERN STAR NAMEPLATES			
DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS			
SINGLE ELECTRIC HORN			
REAR LICENSE PLATE MOUNT END OF FRAME			
DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM			
ROOF MOUNTED LED MARKER LIGHTS			
WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH DUAL CONNECTIONS AT BUMPER			
DAYTIME RUNNING LIGHTS			
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS			
LED SIDE TURN SIGNAL			
C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR			
102 INCH EQUIPMENT WIDTH			
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS			
RH DOWN VIEW MIRROR			
RH AND LH HEATED BLACK HOOD/FENDER MOUNTED SIDE VIEW MIRRORS WITH BLACK MOUNTING ARM	8		
STANDARD SIDE/REAR REFLECTORS			
POLISHED ALUMINUM DIAMOND PLATE WST AFTERTREATMENT SYSTEM COVER			
PARK BRAKE REMINDER WARNING SYSTEM			
NO SLEEPER VENT	-10		
SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH	-10		

<u></u>	Description	Weight Front	Weight Rear	
	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD		11021	
	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR			
Cab Interior			EVIL POTE LES	THE BUILDING
	X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE			
	CHARCOAL BLACK VINYL BASE LEVEL INTERIOR			
	CARBON WITH BASE BLACK ACCENT			
	BLACK MATS WITH ADDED FLOOR HEAT AND NOISE INSULATION			
	(1) DASH MOUNTED POWER OUTLETS AND (1) DUAL USB CHARGING OUTPUT			
	FORWARD ROOF MOUNTED CONSOLE			
	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS			
	(2) COAT HOOKS ON BACKWALL OF CAB			
	NO UPPER BUNK	-50	-50	
	DIGITAL ALARM CLOCK IN DRIVER DISPLAY			
	2-1/2 LB. FIRE EXTINGUISHER SHIPPED LOOSE IN CAB	5		
	STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY			
	RADIATOR MOUNTED AIR CONDITIONER CONDENSER			
	PREMIUM INSULATION			
	PREMIUM LED CAB LIGHTING			
	NO SECURITY DEVICE			
	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
	KEY QUANTITY OF 4			
	LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION			
	BLACK DOOR HANDLES			
	NO MATTRESS	-20	-15	
	TRIANGULAR REFLECTORS WITHOUT FLARES	10		
	PREMIUM 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 2 AIR LUMBAR, INTEGRATED CUSHION EXTENSION, TILT AND ADJUSTABLE SHOCK	20		

Description

Weight Front Weight Rear

BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT

DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS

BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH NO LOGO

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS WITH DRIVER SEAT BELT STATUS INDICATOR LIGHT AND AUDIBLE ALARM

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES

DRIVER AND PASSENGER INTERIOR SUN VISORS WITH ILLUMINATED VANITY MIRRORS

#### **Instruments & Controls**

STANDARD FOOT PEDAL SYSTEM

**ELECTRONIC ACCELERATOR CONTROL** 

ENGINE REMOTE INTERFACE WITH PARK BRAKE INTERLOCK

BRIGHT ARGENT FINISH GAUGE BEZELS

STANDARD CENTER INSTRUMENT PANEL

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

87 DB TO 112 DB SELF-ADJUSTING BACKUP ALARM

ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

MANUAL REMOTE ENGINE STOP/START

PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH 3

 Description	Weight Front	Weight Rear
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
NO PREWIRED HIGH POWER CIRCUIT		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
NO ENGINE OIL TEMPERATURE GAUGE		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
NO OBSTACLE DETECTION SYSTEM		
NO DR ASSIST SYSTEM		
ELECTRONIC STABILITY CONTROL		
NO LANE DEPARTURE WARNING SYSTEM		
1 QUICKFIT PROGRAMABLE MODULE (QPM/XMC)	10	
RAM MOUNT DEVICE PREP: INCLUDES PASS- THROUGH FOR WIRE		
(2) TMC RP1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND PASSENGER SIDE REMOVABLE DASH PANEL (1) CENTER OF OVERHEAD CONSOLE		
TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE		
7" B-PANEL INTERACTIVE TOUCHSCREEN DISPLAY RADIO W/ USB-C, APPLE CARPLAY, ANDROID AUTO, BLUETOOTH/AM/FM/SXM/WB, WITH MICROPHONE		
DASH MOUNTED RADIO		
STANDARD SPEAKER SYSTEM		
NO AM/FM RADIO ANTENNA		
POWER AND GROUND WIRING PROVISION OVERHEAD		
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION		

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY RADIO

Description Weight Weight Description Front Rear

SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD

HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS

INTEROPERABLE SDAR ANTENNA

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

**ELECTRONIC 2500 RPM TACHOMETER** 

DETROIT CONNECT PLATFORM HARDWARE

5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES

NO ASE DATA SVCE EXTENSION

NO EXTENSIONS

IGNITION SWITCH CONTROLLED ENGINE STOP

TWO EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, BLUNTCUT

HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER

HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER

PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS AND SERVICE BRAKES

BW TRACTOR PROTECTION VALVE

DASH MOUNTED TRACTOR AND TRAILER SERVICE BRAKE CHECK WITH HAND CONTROLLED TRAILER BRAKE VALVE

DIGITAL TURBO AIR PRESSURE IN DRIVER DISPLAY

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY

ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS

TWO VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR

SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT

QUICKFIT POWERTRAIN INTERFACE CONNECTOR LOCATED BETWEEN SEATS WITH BLUNTCUTS

Description

Weight Front Weight Rear

4 EXTRA PROGRAMMABLE SWITCHES/INDICATORS

\$B5M5011ZZ,A1A0046ZZ,A1B0194ZZ,A1C0195ZZ

QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) BETWEEN SEATS WITH BLUNTCUTS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

POWDER WHITE (N0006EA) REAR

WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

**BUMPER PAINTED SAME AS CHASSIS** 

**Extended Front Axle Coverage** 

AXLE: DETROIT FRONT ONLY: HD MODERATE 5 YEARS/100,000 MILES/161,000 KM EXTENDED AXLE COVERAGE

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY

Clear Frame Space Details

CFS,LH,OB,#1,START 30" BOC CFS,LH,OB,#1, 36" LONG

Sales Programs

STARQUOTE 47X/49X SALES PROGRAM

TOTAL VEHICLE SUMMARY

Weight Summary

Weight Front

Weight Rear

Total Weight

Application Version 11.9.905 Data Version PRL-29X.014 Town of Munster

10/29/2024 9:03 AM

Factory Weight <sup>+</sup> Total Weight <sup>+</sup>	8647 lbs	7837 lbs	16484 lbs

#### **Extended Warranty**

CUM 2017 L9: HD1 MD DTY 5 YEARS / 100,000 MILES / 161,000 KM EXTENDED WARRANTY. FEX APPLIES

CUM 2017 L9: AT3 MD DTY 5 YEARS / 100,000 MILES / 161,000 KM AFTERTREATMENT. FEX APPLIES

AXLE: NON-DETROIT TANDEM REAR ONLY: HD MODERATE 5 YEAR/100,000 MILE/161,000 KM EXTENDED COVERAGE

TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING COVERAGE \$750 CAP FEX APPLIES

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

### **Russ Kozyra**

Dustin Waters < dustin.waters@delwa.net> From: Wednesday, October 30, 2024 7:49 AM Sent:

Russ Kozyra To: Re: Trade Subject: Trade in amount for \$460 - \$10,000

It's 10,000

Sent from my iPhone

On Oct 30, 2024, at 7:42 AM, Russ Kozyra <rkozyra@munster.org> wrote:

Good morning. Could I please a trade number for the truck. Denny said \$10,000 I just need something in writing. Thanks ASAP Please