## Town of Munster – Parks Department

## BID SPECIFICATION - (1) New 2020 ¾ Ton 4WD Regular Cab 8' Utility Bed Pickup Truck

Truck Specifications:	YES	NO
2020 4WD Regular Cab, 133.6" WB, 8' Bed Pickup, Work Truck		
Suspension Package, Standard	A <del>====</del>	-
Emissions, Federal Requirements		-
Engine, Vortec 6.0L, Variable Valve Timing, V8, SFI, Flexfuel (or equivalent)	· <del></del> ·	
Transmission, 6-Speed Automatic, Heavy Duty, Electronically Controlled		
GVWR 9,500 lbs.		
Rear Axle, 3.73 Ratio. Heavy Duty Automatic Locking Differential	· <del></del>	
Work Truck Preferred Equipment Group	: <del></del> -	
Tires, LT265/70R17 All-Terrain, Blackwall	_	
Paint, Dark Green (woodland green)		
Seats, Front 40/20/40 Cloth Split Bench, 3-Passenger		
Audio System, AM/FM Stereo, Bluetooth for phone		
Snow Plow Prep Package	s <del></del>	
Alternator 220 Amps	-	
Transfer Case Manual shift		
Trailering Package, Heavy Duty, Including Trailer Brake Controller	-	
Skid Plate Package	:====:	
Power Windows and Door Locks	-	
Power Adjustable Outside Heated Trailering Mirrors	<del></del> 1	
Remote Keyless Entry with (3) Transmitters W/Keys	: <del></del> :	
Rear Vision Camera Prep Kit		
Dealey Installed.		
Dealer Installed:		
One Truck Shall Be Fitted With A Boss 8'6" Super Duty Straight Blade Snow Plow.	77	
With Floor Mount Control, Rubber Deflector, LED Lights And Smarthitch 2	4	-
LED Amber 6 Module Mini Lightbar	2	-
LED Arrow Board, Amber, (8) Segment Low Profile and mounted Both Mounted on		
Aluminum cab gaurd	<del></del> 0	
(4) Corner Strobes, LED	:	_
OEM 6" Rectangular Assist Steps – Black		

FIBERGLASS/ALUMIMUN SERVICE BODY <u>DIMENSIONS:</u>	YES NO
SS = 33 / 40 / 23	
CS = 33 / 40 / 23	
FBCA = 53.625	
OL = 96	
OVERALL WIDTH - 82.75	
PACK DEPTH - 15.00	
FLOOR WIDTH - 48.75	
PACK HEIGHT - 42.00	
MOUNTING HEIGHT - 25.00	
CONSTRUCTION:	
ALUMINUM UNDERSTRUCTURE	
ALUM TREAD FLOOR	-
SMOOTH ALUMINUM BULKHEAD	
ALUMINUM TAILSKIRT	/ <del>/</del>
NON-SKID COMPARTMENT TOPS	·
CLEAR VINYL ROCK GUARDS	
BLACK PLASTIC FUEL BEZEL	
REMOVEABLE WHEEL WELL PANELS	
NO BUMPER	
DELETED STANDARD BODY TAILGATE	, <del></del>
BODY SPRING MOUNT KIT	,
COLOR:	
GREEN GELCOAT (CODE TO BE GIVEN AT TIME OF ORDER)	
DOORS:	
STAINLESS STEEL ROTARY LATCH	
TYPE 304 STAINLESS STEEL HARDWARE	
TYPE 304 STAINLESS STEEL DOOR HINGE	
/INYL COVERED S/S CABLE DOOR STOPS	
AUTOMOTIVE GRADE BUBBLE GASKET	
ONE PIECE MOLDED DOORS WITH AUTOMOTIVE FINISH BOTH SIDES	
RECESSED DOOR JAMBS	
LOW THROUGH VENTILATION SYSTEM	
NHITE COMPARTMENT INTERIORS	
RECESSED DOOR SEAL SYSTEM	
IGHTING:	
IGHT ADAPTOR FOR SPECIFIED CHASSIS	
ULL LED LIGHTING PACKAGE - LIFTGATE MOUNT 1 STOP / TAIL / TURN/MARKER	
BACK-UP LIGHTS	
REAR LIGHTS MTD TO OUTER EDGE TO ACCOMMODATE LIFTGATE	
COMPARTMENT LAYOUTS:	
TREETSIDE FRONT COMPT	
ULLOUT DRAWER 5 (1) 7" DEEP (1) 5" DEEP (3) 3" DEEP	
TREETSIDE HORIZONTAL COMPT	
OMPARTMENT BOTTOM TRAY	
OIVIDER PACK - 2" FIBERGLASS - 4 PER PACK	
TREETSIDE REAR COMPT	

	YES	NO
PULLOUT DRAWER 5 (1) 7" DEEP (1) 5" DEEP (3) 3" DEEP	-	
CURBSIDE FRONT COMPT W/ INTERIOR LIGHT GUARD		
ONE ADJUSTABLE SHELF		
ADDITIONAL ADJUSTABLE SHELF		
CURBSIDE HORIZONTAL COMPT		
COMPARTMENT BOTTOM TRAY		
DIVIDER PACK - 2" FIBERGLASS - 4 PER PACK		
CURBSIDE REAR COMPT	-	===
INTERIOR LIGHT GUARD	-	
LIFTGATE		
TRAVEL DISTANCE 42"		
CAPACITY 1300 LBS		-
PLATFORM LOAD WIDTH 49 5/8"		
CLEAR OPENING BETWEEN UPRIGHTS 49 5/8"		
OVERALL PLATFLORM WIDTH 59 3/8"	-	
FRAME WIDTH OUTSIDE OF UPRIGHTS 55"		_
HEIGHT OF PLATFORM ABOVE MAINFRAME 20 1/16"	-	
PLATFORM LOADING DEPTH 38 ½"		
TAPER 6"		_
HEIGHT OF PLATFORM ABOVE UPRIGHTS 3/16"	-	
ALUMIMUN TWO PIECE FOLDING PLATFORM		_
FIXED & TIMES TOGGLE CONTROL	)===;	
150 AMP CIRCUIT BREAKER	:====	_
FULL LENGTH POWER CABLE	) <del></del>	-
MAINTENANCE FREE PINS AND BUSHINGS	_	
DUAL HYDRAULIC CYLINDERS	<u></u> , (	-
FULLY ENCLOSED HYDRAULIC SYSTEM	-	_
PARALLEL-ARMS	-	
INVERTER	-	-
.12 VDC NOMINAL DC INOUT VOLTAGE		
.10.7-16.5 DC INPUT VOLTAGE VOLTAGE		_
.360 MAXIMUM INPUT VOLTAGE	-	_
.NUT & BOLT MG DC INPUT CONNECTIONS .110VAC OR 120VAC OUTPUT VOLTAGE SLECTABLE		-
		-
.20 AMP MAXIMUM OUTPUT CURRENT		-
.60 HZ + OR – 1% OUTPUT FREQUENCY	-	-
.PURE SINE WAVE FORM	-	-
.THD <3% TOTAL HARMONIC DISTORTION	1	
.2200 WATTS MAX OUTPUT FOR 10 MIN – 10% OVER INVERTERS RATE		
WITH CONNTINUOUS WATTAGE		
.2200 WATTS CONTINUOUS OUTPUT POWER		
,4000 WATTS SURGE OUTPUT POWER	-	
.85-90% PEAK EFFICIENCY	-	
.(1) 5V-2.1A USB CHARGING PORT	-	
.(1) GFCI DUPLEX AC OUTPUT COONNECTION	3	
.TERMINAL BLOCK FOR HARDWIRING		
.DIGITAL DISPLAY WITH ERROR CODE		

## TRADE IN VEHICALS

**UNIT # 140** 

2010 GMC 2500 DOUBLE CAB

VIN #1GT5KZBG9AZ230373

MILES 71,225

UNIT #145

2010 CHEVY 2500 REG. CAB

VIN #1G3CKVBGXAF153577

MILES 68,145

Come look at trades weekdays from 7:00 AM till 2:00 PM Address 508 Fisher St. Munster,In 46321 Quote deadline is 2/13/2020

Any questions please contact Director of Munster Parks Greg Vitale (219) 836 -6925